



DA WEST / LOADSTAR

PO Box 968, Friday Harbor, WA. 98250
(360) DIESEL-1 * 1(800)343-7351 * (360)378-4182

WWW.DAWEST.COM
DIESEL EQUIPMENT SOLUTIONS

DPL70-SF2PT MARITIME TRASH PUMP

This LOADSTAR maritime service pump is a self-priming, centrifugal diesel trash pumps feature reliability and materials that will stand up to salty and brackish water. These pumps are assembled using the finest components available. The Yanmar "L" series or Kubota (Tier4) diesels, are popular and proven lightweight 4-cycle air cooled engines. These engines combined with a composite pump end, and a stainless steel frame creates a maritime friendly pump. This high performance diesel trash pump provides the user with safe, easy starting, reliable service and life many times that of gasoline powered counterpart.

SPECIAL FEATURES:

- Tig welded, 1" stainless steel, #304 square tube roll cage frame
- Variable speed governor allowing pump speed to match the job
- Quick release stainless steel housing clamp for fast, easy cleanouts
- Long life oil-resistant heavy service rated internal parts with built-in check valve
- Easy recoil starting with auto decompression release and self-fuel bleed
- Extra tough vibration isolation, and nonskid feet
- This is a lightweight, rugged, diesel pump that works and doesn't break!

ENGINE:

- Model: Yanmar L 70 W Series (Kubota Tier 4 option)
- Single Cylinder, Direct Injected, Naturally Aspirated System
- Internally Balanced, Single Counter Rotating Balancer Shaft
- Unit Mounted Air Filter, Enclosed Paper Element Type
- Engine Mounted Fuel Tank, 3.06 Quart Capacity
- Automatic Bleeding Fuel System
- Pressure & Splash Lubrication, Oil Capacity 1.16 Quarts
- Recoil Starting w/Auto Decompression System
- Engine Mounted Expansion Silencer w/Heat Shield
- Rotatable Exhaust Deflector
- Variable Speed Throttle & Governor
- Combustion system: Direct Injection
- Displacement cc (cu.in.): 320 (12.88)
- Bore x stroke mm (in.): 78X67 (2.76X2.17)
- Engine speed maximum: 3600
- Intermittent Output HP: 6.4

- Dry weight kilos (lbs): 26 (79) Recoil Start Fuel tank cap: 2.7L / 2.85QT
- Lube oil cap: 1.1L / 1.16QT



PUMP:

- LOADSTAR™ Model: DPL70-SF2PT Diesel Trash Pump
- Suction & discharge: 2" FEM-NPT
- Maximum flow: 250 GPM
- Maximum discharge head: 83 FT
- Maximum suction lift: 25 FT
- Maximum spherical solid: 1"
- Bearings: Silicon carbide
- Main pump shaft: Stainless steel sleeve
- Housing: Corrosion Proof Glas/Poly
- Impeller (non-spark): High performance 636

DIMENSIONS:

- Dry weight: 130 LBS
- Length: 24 Inches
- Width: 18 Inches
- Height: 22 Inches

CALL (800) DIESEL-1 FOR A QUOTE