



DA WEST / LOADSTAR
PO Box 968, Friday Harbor, WA.98250
(360) DIESEL-1 * 1(800)343-7351 * (360)378-4182
WWW.DAWEST.COM
DIESEL EQUIPMENT SOLUTIONS

DPK95-FP110 PORTABLE DIESEL FIRE/PRESSURE PUMP

The LOADSTAR maritime, self-priming, centrifugal diesel fire pumps feature quality usually found in heavier and more expensive units. These pumps are assembled using the finest components available. The Kubota(Tier4) diesel engines are popular and proven lightweight single cylinder 4-cycle air cooled engines. They are coupled to a super tough, type approved, USCG compliant fire pump. Excellent for use where higher pressures and general pumping requirements are needed. This high performance diesel saltwater pump provides the user with safe, easy starting, reliable service and life many times that of gasoline powered counterparts. This pump meets and exceeds the criteria for a portable subchapter M pump! Ask us about the new optional all BRONZE pump end!



SPECIAL FEATURES:

- Tig welded, 1" stainless steel, #304 square tube roll cage frame
- Variable speed governor allowing pump speed to match the job
- Long life oil-resistant salt water rated internal parts with built in check valve
- Electric Start with auto de-compression release and self fuel bleed feature
- Stainless steel drive sleeve with self adjusting, severe service, s/s and viton shaft seal
- Replaceable suction valve with stainless steel weights
- Utilizes 2" NPT suction and discharge flanges and gaskets
- Extra tough anti-vibration isolators, and nonskid feet

ENGINE:

- Kubota engine (Tier 4).
- Single Cylinder, Direct Injected, Naturally Aspirated System
- Indirect injection, providing Smooth Operation and Reduced Engine Noise
- Unit Mounted Air Filter, Enclosed Paper Element Type
- Engine Mounted Fuel Tank With 4.7 Liter Capacity
- Auto Bleeding Fuel System
- Pressure and Splash Lubrication, Oil Capacity is 1.7 Liters
- 15 Amp. D.C. Alternator
- Electric Starting With Manual Decompression System
- Engine Mounted Expansion Silencer With Heat Shield
- Rotatable Exhaust Deflector
- Variable Speed Throttle & Governor

CALL (800)DIESEL-1 FOR A QUOTE



DA WEST / LOADSTAR
PO Box 968, Friday Harbor, WA.98250
(360) DIESEL-1 * 1(800)343-7351 * (360)378-4182
WWW.DAWEST.COM
DIESEL EQUIPMENT SOLUTIONS

PUMP:

- LOADSTAR Model: DPK-95 FP110
 - Max GPM Approx : 175 GPM
 - TDH Head (Discharge Pressures) 270'
 - Max Suction Lift Approx: 25 Feet
 - Max Solids Handling Approx: .28 "
 - Self Priming High Pressure Pump
 - Grey Iron Housing & Volute
 - Bronze Impeller – High Pressure
 - Severe Service 316 Stainless Steel Impeller Shaft
- Long Life Silicon Carbide Shaft Seal
 - Built In Check Valve
 - 2" x 2" Suction & Discharge NPT With S/S Discharge Elbow
 - Suction Strainer Included
 - Stainless Steel Fasteners With Ny-Loc Nuts
 - Resilient Isolators Attached For Vibration Control

DIMENSIONS:

- Dry weight: 270 LBS
- Length: 24 Inches
- Width: 20 Inches
- Height: 21 Inches

CALL (800)DIESEL-1 FOR A QUOTE