



DA West / LOADSTAR
PO Box 968, Friday Harbor, WA.98250
(360) DIESEL-1 * 1(800)343-7351 * (360)378-4182
WWW.DAWEST.COM
DIESEL EQUIPMENT SOLUTIONS

HPUK-95 HYDRAULIC POWER PACK

High quality hydraulic power packs, manufactured by Diesel America, fit a wide range of applications from custom units for oil spill cleanup to standard power packs used in construction and rental service.

Built with severe service in mind, only the best components are used in our power pack construction. Quality not only provides the safest operation, but is the most cost-effective solution. The HPUK-95 comes standard with the Kubota engine but is also available with the Yanmar engine.

ENGINE:

- Diesel Power—Kubota OC95 Air/Oil Cooled Diesel Engine.
- EPA Tier 4 Compliant and Certified.
- Electric Start with Interstate DCM 35 AGM Battery.
- Heavy Service 15 Amp 12 Volt Alternator.
- Ring Gear Bendix Type Starter, Heavy Duty, Totally Enclosed
- Automatic Self Bleeding Fuel System.
- Variable Speed Governor with Throttle Lever
- Auto Returning Decompression Lever.
- Shielded High Temperature Surfaces, Muffler, etc.
- Critical Vibration Engine Mounts.
- Key Switch Panel with Glow-Plug Function.
- Extensive Engine Manufacturer's Warranty.

HYDRAULICS:

- Eaton Commercial Heavy Duty Hydraulic Pump
- Panel Mounted Lever Type Flow Control with Relief Valve w/ Feeding Directional Valves.
- Baldwin Heavy Duty Return Filter With Restriction Gauge
- 3 Position Directional Valve- Detent Style or Spring to Neutral - Customer Specified
- 17 Gallon Reservoir with Drain in Base
- Main Workport fittings Quick Disconnect Type Specified by the Customer-Standard.
- Case Drain Port fitting will be specified by customer-Standard
- All Fittings Top Mounted-No Leak Potential, Except Tank Drain
- #316 Stainless Steel Hardware Used Throughout.



TANK BASE:

- Heavy Duty Aluminum #5052-H21 x 3/16" Large Radius Folded & Welded Tank Construction
- 1/2" 5086-T6 Plate Engine Mount Pads (Tank Top).
- Barry Vibration Isolating Mounts to Hold Engine in Place.
- No Side or Bottom Service Penetrations to Leak, Except Drain.
- Pressure Tested 200% Over Standard Specifications
- 12 Volt 5 Amp Continuous Run Hydraulic Cooler Optional
- Aluminum Radiating Tank Surface for Cooling-Intermittent Use.
- 16 Gallons Gross Hydraulic Oil Capacity.
- Top Mounted Inspection & Cleaning Ports.
- Dimensions-28" L x 23"W x TBD" H (Tank Dims may change slightly). Height will be determined by the optional wheel kit.

CALL FOR A QUOTE (800) DIESEL - 1