



DA WEST / LOADSTAR
PO Box 968, Friday Harbor, WA.98250
(360) DIESEL-1 * 1(800)343-7351 * (360)378-4182
WWW.DAWEST.COM
DIESEL EQUIPMENT SOLUTIONS

DPL48-2PFC CHEMICAL PUMP

The LOADSTAR heavy service, self priming, centrifugal chemical pumps feature quality usually found in heavier and more expensive units. These pumps are assembled using the finest components available. The Yanmar "L" series diesel, a popular and proven lightweight 4-cycle air cooled engine, is coupled to the super tough fuel rated pump. This high performance diesel powered chemical pump provides the user with safe, easy starting, reliable service and life many times that of gasoline powered counterparts.



SPECIAL FEATURES:

- Tig welded, 1" stainless steel, #304 square tube roll cage frame
- Variable speed governor allowing pump speed to match the job
- Long life oil-resistant internal parts with built in check valve
- Easy recoil starting with auto compression release and self fuel bleed Extra tough anti-vibration isolator, and nonskid feet
- This is a lightweight, rugged, diesel pump that works and doesn't break!

ENGINE:

- Model: Yanmar L 48 V Series
- Combustion system: Direct Injection
- Displacement cc (cu.in.): 211 (12.88)
- Bore x stroke mm (in.): 70X55 (2.76X2.17)
- Engine speed maximum: 3600
- Output HP: 4.7
- Continuous output HP: 4.2
- Dry weight kilos (lbs): 26 (57)
- Fuel tank cap. L. (gal.): 3.5 (0.92)
- Lube oil cap. L. (gal.): 0.8 (0.21)

PUMP:

- LOADSTAR™ Model: DPL48-2PFC
- Suction & discharge: 2" Male-NPT
- Maximum flow: 170 GPM
- Total dynamic head (max): 80 FT
- Suction lift (max.): 20 FT
- Spherical solids (in.): .25"
- Seal, main : 316 Stainless/Carbon/ Ceramic/ Viton
- Housing, Heavy Duty: 316 Stainless Steel
- Impeller Semi-Open Composite: High performance

DIMENSIONS:

- Dry weight: 105 lbs with recoil start
- Length: 24"
- Width: 18"
- Height: 21"

CALL (800) DIESEL-1 FOR A QUOTE