



**DA WEST / LOADSTAR**  
PO Box 968, Friday Harbor, WA.98250  
(360) DIESEL-1 \* 1(800)343-7351 \* (360)378-4182  
[WWW.DAWEST.COM](http://WWW.DAWEST.COM)  
DIESEL EQUIPMENT SOLUTIONS

## DPL48-3PD-75 DISPLACEMENT PUMP

The Loadstar DPL48-3PD-75 positive displacement pump is a unique and welcome addition to the LOADSTAR pump line-up. This SPATE pump by SELWOOD is coupled to the super tough and reliable Yanmar L48 V Series engine (also available with the HATZ 1B20 tier 4 engine). This diesel pump combination provides the user with a positive displacement pump that has the ability to smoothly and efficiently pump oily water and chemicals. The pump is packaged in a TIG welded aluminum frame, is available with all terrain tires for the difficult to maneuver surfaces and the folding handle allows for easy storage. This Selwood Spate pump has been a favorite in the oil spill clean-up community for decades due to the ability to pump sludge and slurries in skimming operations. Give us a call today to discuss your application.



### ENGINE:

- Yanmar L48 V Series Engine
- Single Cylinder, Direct Injected, Naturally Aspirated System
- Internally Balanced, Single Counter Rotating Balancer Shaft
- Unit Mounted Air Filter, Enclosed Paper Element Type
- Engine Mounted Fuel Tank, 2.5 Quart Capacity
- Automatic Bleeding Fuel System
- Pressure and Splash Lubrication, Oil Capacity is .84 Quarts
- Recoil Starting with Auto Decompression System
- Engine Mounted Expansion Silencer With Heat Shield
- Rotatable Exhaust Deflector
- Cold Weather Start Assist
- Variable Speed Throttle & Governor

- Indefinit Dry Running Capability
- Non-Turbulent Flow
- Easy Start Industrial Centrifugal Clutch/Reduction
- Hose Barb Connections- Cam Lock Whips available.
- Viton Seals

### FRAME:

- TIG Welded Aluminum or Stainless Frame
- Stainless Steel Nylok Hardware Used Throughout
- Single Center Lifting Point, Either Frame
- (Optional Configurations Available Upon Request)
- Frame to Ground Heavy Duty Isolators
- Crated & Shrink Wrapped
- Operators Manual- Additional Manuals available

### PUMP:

- Discharge Flows To 132 GPM
- 43 PSI Max. Discharge Pressure Shut Off 100 feet TDH
- Self priming to 27 feet
- Max Solids handling 0.25"
- Cast Aluminum Construction

**CALL (800)DIESEL-1 FOR A QUOTE**



**DA WEST / LOADSTAR**  
PO Box 968, Friday Harbor, WA.98250  
(360) DIESEL-1 \* 1(800)343-7351 \* (360)378-4182  
[WWW.DAWEST.COM](http://WWW.DAWEST.COM)  
DIESEL EQUIPMENT SOLUTIONS

**DIMENSIONS:**

- Dimensions of Standard Frame:
  - Length: 26 inches
  - Width: 22 inches
  - Height: 24 inches
  - Weight: 170 lbs
- Dimensions with Wheel and Handle Kit:
  - Length: 32 inches
  - Width: 30 inches
  - Height: 30 inches
  - Weight: 170 Lbs.

**CALL (800)DIESEL-1 FOR A QUOTE**